



Pentofrost NF

Environmental friendly Antifreeze for multipurpose application

Description

Pentofrost NF is a modern antifreeze fluid concentrate formulated without nitrite, amine and phosphorous containing additives. Beside its basic feature as a superior antifreeze for water-cooled engines it shows a minimal evaporation loss.

Pentofrost NF does not affect sealings and shows a good corrosion protection for all material used in cooler devices and for non ferrous metals.

Pentofrost NF is easily miscible when blending the cooling fluid down (important!) to a concentration recommend by the car manufacturer. The performance is not affected when chalky water is employed.

Pentofrost NF is miscible with all other quality brand antifreezes of same specification.

Pentofrost NF is low hazardous to water.

Quality Level

AFNOR R-15-601
BS 6580:1992

Product Classification

The product is classified as:
Xn
harmful (if swallowed)

Pentofrost NF		Typical Data	
	Unit	Result	Method
Appearance		clear and blue	DIN 10964
Density at 20 °C	kg/m ³	1100	DIN EN ISO 12185
Freezing Point	°C	-12	ASTM D1177
Mixing Table			
Mixing ratio of Pentofrost NF/water	50 / 50		
Boiling Point	129 °C / 265 °F		
Freezing Point	< -37 °C / -34 °F		

While handling antifreezes the relevant safety rules have to be taken into account. For more detailed information please see the current safety data sheet for this product.