



RAVENOL CVTF NS2/J1 Fluid



ART.-NR. 1211114

1 L | 1211114-001
4 L | 1211114-004
10 L | 1211114-010
20 L | 1211114-020
20 L | 1211114-B20
60 L | 1211114-060
60 L | 1211114-D60
208 L | 1211114-208
208 L | 1211114-D28
1000 L | 1211114-700

FABRICATION SYNTHETIC

RECOMMENDATIONS NISSAN KLE52-0002 | NISSAN CVT NS-2 | NISSAN KLE52-0004 | MITSUBISHI S0001401 | PSA STANDARD 9735EF | SUZUKI CVT FLUID GREEN-1 99000-22B15-046

RAVENOL CVTF NS2/J1 Fluid is a synthetic CVTF (Continuously Variable Transmission Fluid) produced on the basis of high-quality hydrocrack oils with special additives and inhibition which guarantees a perfect function of the CVT transmission.

RAVENOL CVTF NS2/J1 Fluid is a CVTF of the latest generation. It is especially developed for the CVT transmission of JATCO. It guarantees in any mode for maximum wear protection.

RAVENOL CVTF NS2/J1 Fluid is green coloured.

Application Notes

RAVENOL CVTF NS2/J1 Fluid is suitable for use in CVT transmission of following vehicles with CVT-Transmission:

Peugeot 4007, Citroen C-Crosser, Mitsubishi Outlander, Mitsubishi Delica D5, Mitsubishi Galant Fortis, Mitsubishi RVR, Mitsubishi Lancer 1.8 CY0 2007, Nissan Murano, Nissan Teana, Nissan Maxima, Nissan Presage, Nissan X-Trail, Nissan Lafesta, Nissan Serena, Nissan Bluebird Sylphy, Nissan Dualis, Suzuki Kizachi, Suzuki SX4, Dodge Caliber, Jeep Compass, Jeep Patriot and other models with CVT-transmission JATCO JF011E (RE0F10A; F1CJA) or JF010E (RE0F09A).

Maintenance-filling under normal operating conditions.

Characteristics

RAVENOL CVTF NS2/J1 Fluid offers:

- Very good lubricating ability even at low temperatures in winter
- A high, stable viscosity index
- Very good oxidation stability
- Protection against corrosion and foam formation



- Good balanced coefficient of friction
- A high thermal and oxidative stability
- An excellent cooling capacity

RAVENOL special transmission fluid is special development for special gear and cannot be selected on the basis of technical parameters (viscosity, etc.). Therefore the decision was made not to give technical data. Please note: RAVENOL special transmission fluid is exclusively to apply under the original number, as indicated in the

product information. Not sure of the correct transmission fluid, you can ask your garage or the car dealer with respect to the original OEM gear type and number or consult

our advisers. It must be specified the VIN code (Vehicle Identification Number) of your vehicle. Misapplication of RAVENOL special transmission fluid can lead to

malfunction of the transmission shifting problems, increased fuel consumption, unwanted slip behavior, etc. cause and cause the failure of the transmission. Ravensberger

Schmierstoffvertrieb GmbH does not liable for transmission failures in case of wrong selection of RAVENOL special transmission fluid.



Property	Unit	Data	Audit
Density at 20°C	kg/m ³	838,0	EN ISO 12185
Colour		grün	visual
Pourpoint	°C	-51	DIN ISO 3016

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

Release: : 16. January 2020