

## RENOLIN UNISYN XT

**Fully-synthetic industrial gear lubricants based on polyalphaolefins of the latest generation, very high natural, shear stable viscosity index**

### Description

The products of the RENOLIN UNISYN XT series are demulsifying, fully-synthetic industrial gear oils with elevated aging resistance, excellent load-carrying capacity and wear protection, based on polyalphaolefins of the latest generation. RENOLIN UNISYN XT oils show good resistance to micropitting. Reliable lubrication of roller bearings is confirmed by the good results of the FE8 testing. Moreover the RENOLIN UNISYN XT oils show a good filterability. The products are preferably used when increased requirements are set for high and low operating temperatures. Especially in low temperature areas RENOLIN UNISYN XT shows significant advantages in comparison to conventional PAO based industrial gear oils. In gearboxes and circulating systems with sump temperatures up to 90 °C, longer oil-change intervals in comparison with previous mineral oils are achieved.

Miscibility with gearbox oils based on mineral oil and PAO is generally given, which means that simplified conversion to RENOLIN UNISYN XT is possible. Nevertheless a complete change-over is recommended (perhaps with flushing procedure) to receive the full performance of RENOLIN UNISYN XT and especially to exploit the advantages in comparison to conventional oils.

### Advantages

- **Excellent low temperature behaviour**
- **Low foaming**
- **Good air release capacity**
- **Very good aging resistance**
- **Excellent corrosion protection**
- **Excellent viscosity-temperature behavior**
- **Very high natural VI (viscosity index)**
- **Multigrade character**
- **Excellent wear protection, high EP performance**
- **Miscible with mineral oil- and ester-based gear oils**
- **Prolongation of the service intervals possible**
- **For high and low operating temperatures**

## RENOLIN UNISYN XT

**Fully-synthetic industrial gear lubricants based on polyalphaolefins of the latest generation, very high natural, shear stable viscosity index**

### Application

The oils of the RENOLIN UNISYN XT series are used for all applications in industry where a synthetic oil of the CLP type according to DIN 51517-3 is recommended by the manufacturer. Highly-stressed bearings, joints, pressure screws, spur gears, worm gears and planetary gears can be reliably, safely and economically supplied even at short-term peak temperatures up to 150 °C. RENOLIN UNISYN XT can particularly be used if high low temperature demands for the gear oil are required.

### Specifications

The products meet and in many cases exceed the requirements according to:

- DIN 51517-3: CLP
- ISO 6743-6 and ISO 12925-1:  
CKC / CKD / CKE / CKSMP
- AGMA 9005/E02: EP
- AIST 224
- Flender approval according to Flender BA 7300, Table A

## RENOLIN UNISYN XT

Fully-synthetic industrial gear lubricants based on polyalphaolefins of the latest generation, very high natural, shear stable viscosity index

### Typical technical data:

Product name	RENOLIN UNISYN XT					Test method
	68	100	150	220		
Properties	Unit					
ISO VG		68	100	150	220	DIN 51519
Kinematic viscosity						
at - 20 °C	mm <sup>2</sup> /s	3,600	5,850	9,250	13,670	DIN EN ISO 3104
at - 10 °C	mm <sup>2</sup> /s	1,360	2,080	3,100	4,400	
at 0 °C	mm <sup>2</sup> /s	630	950	1,500	2,300	
at 40 °C	mm <sup>2</sup> /s	68	100	150	220	
at 100 °C	mm <sup>2</sup> /s	11.0	15.3	21.4	29.4	
Viscosity index	-	154	162	168	174	DIN ISO 2909
Density at 15 °C	kg/m <sup>3</sup>	850	850	850	860	DIN 51757
Colour	ASTM	0.5	0.5	0.5	0.5	DIN ISO 2049
Flashpoint in open cup acc. to Cleveland	°C	238	238	238	242	DIN ISO 2592
Pourpoint	°C	-54	-48	-45	-42	DIN ISO 3016
Neutralisation number	mgKOH/g	0.86	0.86	0.86	0.86	DIN 51558
Demulsibility at 82 °C	min	< 10	10	15	20	DIN ISO 6614
Scuffing and scoring test, FZG A/8.3/90	failure load stage			>14		DIN ISO 14635-1
Micropitting load capacity C/8.3/90	GF Class	-	-	GFT high, >10		FVA 54/I-IV
C/8.3/60	GF Class	-	-	GFT high, >10		FVA 54/I-IV
FE8 roller bearing wear test, D-7.5/80-80						DIN 51819-3
- roller element wear	mg			1.0		
- cage wear	mg			<100		

## RENOLIN UNISYN XT


Fully-synthetic industrial gear lubricants based on polyalphaolefins of the latest generation, very high natural, shear stable viscosity index

### Typical technical data:

Product name	RENOLIN UNISYN XT					Test method
	320	460	680	1000		
Properties	Unit					
ISO VG		320	460	680	1000	DIN 51519
Kinematic viscosity						
at - 20 °C	mm <sup>2</sup> /s	19,400	41,000	130,000	187,000	DIN EN ISO 3104
at - 10 °C	mm <sup>2</sup> /s	6,000	11,500	35,300	48,000	
at 0 °C	mm <sup>2</sup> /s	3,500	5,600	8,500	15,000	
at 40 °C	mm <sup>2</sup> /s	320	460	680	1,000	
at 100 °C	mm <sup>2</sup> /s	40.2	54.5	75.5	101.0	
Viscosity index	-	179	188	192	195	DIN ISO 2909
Density at 15 °C	kg/m <sup>3</sup>	860	860	860	860	DIN 51757
Colour	ASTM	0.5	0.5	1.0	1.0	DIN ISO 2049
Flashpoint in open cup acc. to Cleveland	°C	242	242	244	244	DIN ISO 2592
Pourpoint	°C	-42	-39	-39	-33	DIN ISO 3016
Neutralisation number	mgKOH/g	0.86	0.86	0.86	0.86	DIN 51558
Demulsibility at 82 °C	min	20	25	25	40	DIN ISO 6614
Scuffing and scoring test FZG A/8.3/90	failure load stage		>14			DIN ISO 14635-1
FZG A/16.6/90	failure load stage		>14			DIN ISO 14635-1
Micropitting load capacity C/8.3/90	GF Class		GFT high, >10			FVA 54/I-IV
C/8.3/60	GF Class		GFT high, >10			FVA 54/I-IV
FE8 roller bearing wear test, D-7.5/80-80						DIN 51819-3
- roller element wear	mg		1.0			
- cage wear	mg		<200			


## RENOLIN UNISYN XT

Fully-synthetic industrial gear lubricants based on polyalphaolefins of the latest generation, very high natural, shear stable viscosity index



## RENOLIN UNISYN XT


Fully-synthetic industrial gear lubricants based on polyalphaolefins of the latest generation, very high natural, shear stable viscosity index






## RENOLIN UNISYN XT

Fully-synthetic industrial gear lubricants based on polyalphaolefins of the latest generation, very high natural, shear stable viscosity index



## RENOLIN UNISYN XT

Fully-synthetic industrial gear lubricants based on polyalphaolefins of the latest generation, very high natural, shear stable viscosity index





The information contained in this product information is based on the experience and know-how of FUCHS SCHMIERSTOFFE GMBH in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible. Our products must not be used in aircrafts/spacecrafts or their components, unless such products are removed before the components are assembled into the aircraft/spacecraft. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application.

We therefore recommend that you consult a FUCHS SCHMIERSTOFFE GMBH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care.

Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid.

Any form of reproduction requires express prior written permission from FUCHS SCHMIERSTOFFE GMBH.

© FUCHS SCHMIERSTOFFE GMBH. All rights reserved.

Die Angaben in dieser Produktinformation beruhen auf den allgemeinen Erfahrungen und Kenntnissen der FUCHS SCHMIERSTOFFE GMBH in der Entwicklung und Herstellung von Schmierstoffen und entsprechen unserem heutigen Wissensstand. Die Wirkungsweise unserer Produkte ist von vielfältigen Faktoren abhängig, insbesondere vom konkreten Einsatzzweck, der Applikation der Produkte, den Betriebsbedingungen, der Bauteilvorbehandlung, eventuellem Schmutzanfall von außen, etc. Aus diesem Grund sind allgemeingültige Aussagen zur Funktion unserer Produkte nicht möglich. Unsere Produkte dürfen nicht in Flugzeugen oder Raumfahrzeugen verwendet werden. Zur Herstellung von Komponenten für Flugzeuge oder Raumfahrzeuge dürfen unsere Produkte verwendet werden, wenn sie vor der Montage in das Flugzeug oder Raumfahrzeug rückstandslos von den Komponenten entfernt werden. Die Angaben in dieser Produktinformation stellen allgemeine, nicht verbindliche Richtwerte dar. Keinesfalls beinhalten sie hingegen eine Zusicherung von Eigenschaften oder eine Garantie für die Eignung des Produkts für den Einzelfall.

Wir empfehlen daher, vor dem Einsatz unserer Produkte mit den Ansprechpartnern der FUCHS SCHMIERSTOFFE GMBH ein individuelles Beratungsgespräch über die Einsatzbedingungen in der Anwendung und die Leistungsmerkmale der Produkte zu führen. Dem Anwender obliegt es, die Produkte in der vorgesehenen Anwendung auf deren Funktionssicherheit zu testen und mit der gebotenen Sorgfalt einzusetzen.

Unsere Produkte werden kontinuierlich weiterentwickelt. Deshalb behalten wir uns das Recht vor, das Produktprogramm, die Produkte und deren Herstellungsprozesse sowie alle Angaben in dieser Produktinformation jederzeit und ohne Vorankündigung zu ändern, sofern keine kundenspezifischen Vereinbarungen existieren, die dem entgegenstehen. Alle früheren Veröffentlichungen verlieren mit Erscheinen dieser Produktinformation ihre Gültigkeit.

Vervielfältigungen jeder Art und Form bedürfen der vorherigen schriftlichen Genehmigung der FUCHS SCHMIERSTOFFE GMBH.

© FUCHS SCHMIERSTOFFE GMBH. Alle Rechte vorbehalten.