

SILKOLENE V-TWIN SAE 20W-50

A dedicated range of high performance motorcycle lubricants formulated for V-Twin designs

Description

SILKOLENE V-TWIN 20W-50 is formulated on highly refined mineral base oils and performance additives specifically for Harley Davidson and Metric V-Twins where a 20W-50 is specified.

SILKOLENE V-TWIN 20W-50 provides high levels of engine cleanliness and protects engine components from wear and corrosion.

Specifications / Approvals

- API CF / SG / SH / SJ
- JASO MA & MA2

Advantages/Benefits

- Excellent wear, corrosion and oxidation Protection
- Protects over a wide range of operating temperatures and conditions
- Promotes a high level of engine cleanliness
-
- Keep critical engine components operating at maximum efficiency

PI60387e, PMA, 03.09.2018



Silkolene[®]
SUPERIOR MOTORCYCLE OILS

TECHNICAL DATA

TYPICAL DATA: SILKOLENE V-TWIN SAE 20W-50

Characteristics	Test Method	Unit
Colour	Visual	Dark amber
Specific Gravity at 15°C	IP160	0.891
Kinematic Viscosity at 40°C	IP71	168.4 mm ² /s
Kinematic Viscosity at 100°C	IP71	19.1 mm ² /s
Viscosity Index	IP226	129
Flash Point (Closed up)	IP34	200 °C
Pour Point	IP15	-25 °C

PI60387e, PMA, 03.09.2018

FUCHS SCHMIERSTOFFE GMBH
Friesenheimer Straße 19
68169 Mannheim/Germany

Phone +49 621 3701-0
Fax +49 621 3701-7000
zentrale@fuchs-schmierstoffe.de



Silkolene[®]
SUPERIOR MOTORCYCLE OILS

TECHNICAL DATA

The information contained in this product information is based on the experience and know-how of FUCHS SCHMIERSTOFFE GMBH in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible. Our products must not be used in aircrafts/spacecrafts or their components, unless such products are removed before the components are assembled into the aircraft/spacecraft. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application.

We therefore recommend that you consult a FUCHS SCHMIERSTOFFE GMBH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care.

Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid.

Any form of reproduction requires express prior written permission from FUCHS SCHMIERSTOFFE GMBH.

© FUCHS SCHMIERSTOFFE GMBH. All rights reserved.