



## SILKOLENE COMP 4 XP RANGE

### Extreme Performance Semi-Synthetic Ester Engine oils

#### Description

The SILKOLENE COMP 4 XP RANGE of motorcycle engines oils are designed using XP Technology for high performance On-Road and Off-Road 4 stroke motorcycle engines. XP Technology uses an innovative highly shear stable, low volatility base oil formulation along with stable esters to achieve increased power, provide ultimate engine and transmission protection, reduce oil consumption and improve fuel economy even under race conditions. XP Technology combats engine wear and reduces friction on all critical load surfaces at both high temperature operation and on cold starts.

#### Application

Formulated to meet the needs of both air and watercooled 4-Stroke engines the SILKOLENE COMP 4 XP RANGE comes in four grades and is suitable for 4-Stroke engines fitted to both On-Road and Off-Road motorcycles.

**SILKOLENE COMP 4 10W-30 XP**  
**SILKOLENE COMP 4 10W-40 XP**  
**SILKOLENE COMP 4 15W-50 XP**

#### Specifications / Approvals

- JASO MA2
- API SL Performance

#### Advantages/Benefits

- One product range suitable for all high performance 4-stroke motorcycle engines On-Road and Off-Road
- Superior shear stability produces “stay in grade” synthetic ester containing multigrade engine oils
- Provides a high degree of anti-wear performance for stressed components
- Provides enhanced high temperature deposit control resulting in a cleaner engine and thus promoting longer engine life and performance retention
- Suitable for gearboxes and transmissions where engine oil technology is specified providing good pitting protection
- Balanced frictional properties give precise clutch control / operation
- Also provides good corrosion protection, better oxidation/ nitration resistance and lower volatility than conventional products

PI60579e, PMA, 03.12.2019



**Silkolene**<sup>®</sup>  
SUPERIOR MOTORCYCLE OILS

**TECHNICAL DATA**

## TYPICAL DATA: SILKOLENE COMP 4 XP RANGE

SILKOLENE Comp 4 ...	Test Methode	10W-30 XP	10W-40 XP	15W-50 XP
Appearance	Visual	Amber	amber	amber
SAE Rating		10W-30	10W-40	15W-50
Specific Gravity at 15°C	IP160	0.864	0.866	0.875
Kinematic Viscosity at 40°C	IP71	73.5	103.6	134.2
Kinematic Viscosity at 100°C	IP71	11.6	15.5	18.3
Viscosity Index	IP226	152	158	153
Pour Point	IP15	-36	-36	-36 °C

**FUCHS SCHMIERSTOFFE GMBH**  
Friesenheimer Straße 19  
68169 Mannheim/Germany

Phone +49 621 3701-0  
Fax +49 621 3701-7000  
zentrale@fuchs-schmierstoffe.de

PI60579e, PMA, 03.12.2019

**XP**  
TECHNOLOGY



**Silkolene**<sup>®</sup>  
SUPERIOR MOTORCYCLE OILS

**TECHNICAL DATA**

The information contained in this product information is based on the experience and know-how of FUCHS SCHMIERSTOFFE GMBH in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible. Our products must not be used in aircrafts/spacecrafts or their components, unless such products are removed before the components are assembled into the aircraft/spacecraft. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application.

We therefore recommend that you consult a FUCHS SCHMIERSTOFFE GMBH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care.

Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid.

Any form of reproduction requires express prior written permission from FUCHS SCHMIERSTOFFE GMBH.

© FUCHS SCHMIERSTOFFE GMBH. All rights reserved.

**FUCHS SCHMIERSTOFFE GMBH**  
Friesenheimer Straße 19  
68169 Mannheim/Germany

Phone +49 621 3701-0  
Fax +49 621 3701-7000  
zentrale@fuchs-schmierstoffe.de

**XP**  
TECHNOLOGY