



TITAN UNIVERSAL HD SAE 15W-40

High Performance Engine Oil for mixed fleets operated under normal conditions. Good performance in normally aspirated and turbocharged diesel engines.

Description

TITAN UNIVERSAL HD 15W-40 is the ideal universal engine oil for mixed fleets which should, if possible, be operated on **one** type of engine oil. During the development of TITAN UNIVERSAL HD 15W-40, a special emphasis was given to excellent performance in normally aspirated and turbocharged diesel engines.

Application

TITAN UNIVERSAL HD 15W-40 can be safely used in older engines. Prior flushing is not necessary. In addition to the rationalization which this product allows, TITAN UNIVERSAL HD 15W-40 also ensures that the optimum operating viscosity is maintained at all times, thus reducing power loss and fuel consumption and in turn increasing efficiency. The use of high-capacity by-pass oil filters with TITAN UNIVERSAL HD 15W-40 may also allow oil and filter change intervals to be harmonized. Transmissions with wet brakes are not to be filled with TITAN UNIVERSAL HD 15W-40. TITAN UNIVERSAL HD 15W-40 is miscible and compatible with conventional branded engine oils. However, mixing with other engine oils should be avoided in order to fully utilize the product's benefits. A complete oil change is recommended when converting to TITAN UNIVERSAL HD 15W-40. For information on product safety and proper disposal please refer to the latest Material Safety Data Sheet.

Advantages/Benefits

- Protection against wear event at continuous full-power operation.
- Protection against coking, lacquering, gumming and sludging at extremely high operating temperatures.
- Protection against "bore polishing" and corrosion.
- Minimal oil consumption
- Transmission and hydraulic systems in vehicles and industrial machinery which should be run on Heavy Duty SAE 15W, 15W-30, 15W-40, 20W-20, 20W-30, 20W-40 and 30 engine oils can be operated on TITAN UNIVERSAL HD 15W-40 with excellent results.

Specifications

- ACEA A3/B3/B4
- API CG-4/CF/SL

Approvals

- DEUTZ DQC I-02
- MAN 271
- MB-APPROVAL 228.1 / 229.1
- MTU DDC TYPE-2

FUCHS Recommendations

- ACEA E2
- MIL-L-2104 E
- ALLISON C-4
- CASE MS 1120
- DAF
- MACK EO-L
- NH 330 G
- SCANIA
- STEYR A-202
- VOLVO VDS
- VW 501 01/505 00

PI60021e, PMA, 24.10.2013, Page 1



TYPICAL CHARACTERISTICS

Density at 15 °C	DIN 51757	0.884 g/ml
Kinematic Viscosity at 40°C	DIN 51562-1	107.0 mm ² /s
Kinematic Viscosity at 100°C	DIN 51562-1	14.6 mm ² /s
Viscosity-Index	DIN ISO 2909	141
Flash Point, CoC	DIN ISO 2592	230 °C
Pour Point	DIN ISO 3016	-37 °C



The information contained in this product information is based on the experience and know-how of FUCHS EUROPE SCHMIERSTOFFE GMBH in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pretreatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application.

We therefore recommend that you consult a FUCHS EUROPE SCHMIERSTOFFE GMBH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care.

Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid.

Any form of reproduction requires express prior written permission from FUCHS EUROPE SCHMIERSTOFFE GMBH.

© FUCHS EUROPE SCHMIERSTOFFE GMBH. All rights reserved.